



Product specification sheet

Product title | 3SKB-R916U24 SKB 16U Industrial Shock Mount Rack



Description

3SKB 24? Shock Racks will keep your equipment safe and working while you travel in harsh conditions where your case and devices may be exposed to rough weather, mistreatment, and abuse. These cases are roto-molded to provide excellent strength, durability, and protection. The hinged doors are user friendly with a gasket seal that makes the case water resistant and keeps your gear dry! The supplied caster kit ensures that transport has never been easier?no more heavy lifting and carrying. For efficient and secure transport, these Shock Racks stack perfectly even with the casters mounted! These 24? deep rack models are suitable for IT equipment such as routers, switches, storage and communication devices. Additional applications are in military, security, outdoor, broadcast and many more markets.

Features

- Patent pending compound hinged doors ensure easy opening & closing
- Gasket-sealed doors keep your devices dry & safe
- Smart design provides enough space for air circulation & heat dissipation
- Threaded steel rails offer enhanced durability
- Rear rack rails for even more secure fixing of your equipment
- No more heavy lifting? castor kit standard included
- Cases are shock & water resistant for added protection
- A built-in pressure relief valve helps to maintain an ideal environment at any altitude
- Cases stack superbly with the wheels on or off for efficient & secure transport
- Stainless steel recessed latches provide extra durability

Specifications

• Interior Length	61.0 cm	24.1 inch
• Interior Width	48.3 cm	19.1 inch
• Interior Height	71.1 cm	28.0 inch
• Base Depth	11.4 cm	4.5 inch
• Lid Depth	11.4 cm	4.5 inch
• Exterior Length	90.8 cm	35.8 inch
• Exterior Width	67.3 cm	26.5 inch
• Exterior Height	95.3 cm	37.6 inch
• Carton Length	91.4 cm	36.0 inch
• Carton Width	68.6 cm	27.1 inch
• Carton Depth	99.1 cm	39.1 inch
• Rack Depth	61.0 cm	24.1 inch
• Depth Front Rail to Rail	61.0 cm	24.1 inch
• Depth Front Rail to Back Lid	72.4 cm	28.6 inch
• Shipping Weight	58.1 kg	128.1 lb
• Product Weight	53.4 kg	117.7 lb
• ATA Rated		
• Rack Units: 16		