

# AEGIS™ CASES

## AEGIS AE22070-32.43 FT Specifications



### Case dimensions

|                     |                      |   |     |   |     |    |
|---------------------|----------------------|---|-----|---|-----|----|
| Internal Dimensions | 2100                 | x | 600 | x | 563 | mm |
| External Dimensions | 2200                 | x | 700 | x | 750 | mm |
| Internal Volume     | 0.709 m <sup>3</sup> |   |     |   |     |    |
| Buoyancy In Water   | 709 Kg               |   |     |   |     |    |

### Base dimensions

|                     |      |   |     |   |     |    |
|---------------------|------|---|-----|---|-----|----|
| Internal Dimensions | 2100 | x | 600 | x | 201 | mm |
| External Dimensions | 2200 | x | 700 | x | 321 | mm |

### Lid dimensions

|                     |      |   |     |   |     |    |
|---------------------|------|---|-----|---|-----|----|
| Internal Dimensions | 2100 | x | 600 | x | 362 | mm |
| External Dimensions | 2200 | x | 700 | x | 429 | mm |

|                               |                                  |
|-------------------------------|----------------------------------|
| Case Material                 | Rotomoulded Polyethylene (LLDPE) |
| Latch Material                | Blackened Stainless Steel        |
| Gasket Material               | Silicone Sponge                  |
| Rivet Material                | Stainless Steel                  |
| Minimum Operating Temperature | -40 °C (-40 °F)                  |
| Maximum Operating Temperature | +70 °C (+158 °F)                 |
| Approx. Weight                | 59 Kg                            |

### Standard colour range

Aegis Cases are generally provided in Black, Olive Drab or Portland Stone. Subject to availability other standard colours or bespoke colours are available subject to MOQ.



### Testing and Approvals:

MIL-STD-810G, STANAG 4280, STANAG 4340, IP67, ATA 300  
Def Stan 81-144, Def Stan 00-035 Part 3, Def Stan 81-041 Part 4.

Dimensional Tolerances +/- 1% of stated dimensions